




Part # 11502401 -2010-2015 Camaro



Recommended Tools



2010-2015 Camaro Front AirStrut Installation Instructions


Table of contents

- Page 2..... Included components
- Page 3..... Disassembly and Getting Started
- Page 4..... Strut Installation
- Page 5..... Assembly
- Page 6..... Final Assembly
- Page 7..... Strut Adjustment



Included ComponentsIn the box

Item #	Part #	Description	QTY
1	986-10-055	Strut Cartridge	2
2	90002367	Bearing Retaining Plate	2
3	90002363	Upper Retention Plate	2
4	70011968	Strut Extrusion	2
5	90002368	Thrust Bearing Adapter	2
6	70010987	Thrust Bearing	2
7	70010988	Thrust Bearing Washer	4
8	90001042	COM Bearing	2
9	90000805	COM Bearing Snap Ring	2
10	99562003	9/16"-18 Nylok Jam Nut	2
11	99251007	1/4"-20 x 1/4" SHCS	6
12	99251010	1/4"-20 x 1" SHCS	6
13	038-01-035	Strut Retaining Ring	2
14	99055000	M5 x.8 x 5mm Set Screw	2
15	234-00-153	Locking Ring	2
16	70010991	ABS Line Tab	2
17	70010990	Driver Brake Line Tab	1
17	70011386	Pass Brake Line Tab	1
18	70010975	Sway Bar Link Mount	2
19	99371042	3/8"-16 x 1" SHCS	4
20	99251008	1/4"-20 x 1/2" SHCS	4
21	99251009	1/4"-20 x 3/4" SHCS	6
22	99253011	1/4" Belleville Locking Washer	6
23	21090798	Strut Air Spring	2
24	70012986	Strut Spacer Shim	4
25	99253007	1/4" Split Lock Washer	4
	90002376	Posilink Spacer (Not Shown)	2
	90002571	10mm 90 Degree PosiLink	4
	90002157	T-bushing-Posilink to sway bar	4
	31954201	1/4" 90 Degree Fitting	2






Disassembly

1. Remove the front struts by first disconnecting the ABS wire and brake line(retain hardware) from the factory strut.
2. Disconnect the swaybar linkage from the strut.
3. Support the front hub and control arm assembly and remove the (2) struts bolts(retain hardware) that attach the strut to the spindle.
4. Remove the cap from the top strut nut in the engine compartment, then remove the nut and strut retainer. **DO NOT REMOVE THE SECOND NUT.**
5. Remove strut assembly from the car.


Getting Started

6.



6. The upper strut mount provided in this kit has 2 mounting positions. Centered and offset. Looking at the illustration you will notice "A" bolt holes are centered and "B" bolt holes are offset. Position "A" is used for a street driving alignment. Position "B" is used when a more aggressive alignment is desired. This adjustable upper mount along with the adjustment on the lower Strut mount provide more adjustment than the stock setup. Position "B" will offset the top of the Strut towards the engine.


7.




7. Bolt the upper mount into the car positioning it for the alignment desired using the description in the previous step. The mount will be either centered or the center strut mount offset towards the engine. The upper plate has (6) holes. (3) are threaded and (3) are thru drilled. The long bolts go thru the upper mount to attach it to the lower mount. The short bolts thread into the threaded holes. Tighten all (6) down.



Strut Installation




8. The hood support mount on the passenger strut tower is shaped differently through the years. If your mount interferes with the upper strut mount, it will need to be trimmed. You can use the upper strut mount as a template to mark the mount. We use a die-grinder with a cut off wheel to trim it back. Be sure to protect the car from flying debris when trimming the mount.



9. Install the Air fitting into the Airspring using thread tape. Remove the Adjuster Knob from the Strut shaft for assembly. Bolt the strut assembly into the upper mount (A), see diagram 10 for assembly order.

- 1. Torrington Bearing Race
- 2. Torrington Bearing
- 3. Torrington to Bearing Adapter
- 4. 9/16" Locknut

Assemble components and install into upper mount tightening upper nut. Reinstall upper adjustment knob. Skip to Step 12.




10. Slide the lower strut mount onto the spindle. Insert a Shim Spacer between the Spindle and Extrusion on each side of the Spindle. Align the all of the bolt holes, insert the Factory hardware to attach.

NOTE: These bolts are torque-to-yield bolts. They only have a few adjustments in them before they should be replaced. Tighten the bolt to 60 ft/lbs and turn the nut 180°.




Assembly

11.



11. The Kit includes 4 shims. A shim will need to be placed on each side of the spindle, between the spindle and each ear of the strut mount.

12.




12. Attach the PosiLinks between the strut and Sway bar using the 10mm Nylok Nut. Refer to **Images 11 & 12** for orientation.

NOTE: There is a Drivers and Passenger Posilink assembly, refer to diagrams (11 and 12) for proper installation

NOTE: Some vehicles have a 10mm sway bar linkage, some have 12mm linkage. The Posilink linkage provided in the kit has 10mm studs, T-bushings are provided in the kit for 12mm linkage setups. Install a T-bushing in each side of the swaybar hole, then install the Posilink in it and tighten.

13.



13. The PosiLink mounts with the stud on the Strut pointing forward, and the stud on the Sway bar pointing in.

Note: Image is viewing from front of vehicle.

Note: Depending on the manufacture of the swaybar on your car, you may have to flip the PosiLink assembly to get the best fit. The PosiLink needs to be as straight as possible with the steering wheel straight.



Final Assembly

14.



14. Attach the brake line to the mount on the Strut using the Factory hardware.

15.



15. Slide the ABS wire into its mount on the Strut.

16. Route the Airline to the Air Spring. When hooking up the Airline be sure that you can turn the steering from lock to lock with out tugging on the Airline. This situation will eventually cause the line to leak.

17. Repeat previous steps on Passenger side.



Strut Adjustment

Strut Adjustment 101- Single Adjustable

Rebound Adjustment:

How to adjust your new struts.

The rebound adjustment knob is located on the top of the Strut protruding through the upper mount.

You must first begin at the ZERO setting, then set the shock to a medium setting of 12.



-Begin with the Strut adjusted to the ZERO rebound position (full stiff). Do this by rotating the rebound adjuster knob clockwise until it stops.

-Now turn the rebound adjuster knob counter clock wise 12 clicks. This sets the shock at 12. (settings 21-24 are typically too soft for street use).

Take the vehicle for a test drive.



-If you are satisfied with the ride quality, do not do anything, you are set!

-If the ride quality is too soft increase the damping effect by rotating the rebound knob clock wise 3 clicks.

Take the vehicle for another test drive.



-If the vehicle is too soft increase the damping effect by rotating the rebound knob clock wise 3 additional clicks.

-If the vehicle is too stiff rotate the rebound adjustment knob counter clock wise 2 clicks and you are set!

Take the vehicle for another test drive and repeat the above steps until the ride quality is satisfactory.

Note:

One end of the vehicle will likely reach the desired setting before the other end. If this happens stop adjusting the satisfied end and keep adjusting the unsatisfied end until the overall ride quality is satisfactory.